



M10 THREAD  
(TYP 12 PLACES)

1/4" B.S.P.P. THREAD

Ø100 O.D. OUTLET

100 N.B. FLANGED INLET

M12 THREAD  
(TYP 4 PLACES)

- NOTES!**  
 1. ALL DIMENSIONS IN mm UNLESS OTHERWISE NOTED.  
 2. WORKING / TEST PRESSURE:- 4 BAR / 6 BAR.

5					THIS DOCUMENT IS THE PROPERTY OF GHT - AUSTRALIA P/L. NO EXPLOITATION OR TRANSFER OF ANY INFORMATION CONTAINED HEREIN IS PERMITTED WITHOUT THE WRITTEN CONSENT OF GHT - AUSTRALIA P/L.		DRAWN: W.Y.W. DATE: 24-11-2022 CHECKED:	TITLE: SANDVIK LH621i U/G LOADER CHARGE AIR COOLER - 1663 x 442 x 160 ARRANGEMENT			
4											
3											
2											
1											
No	DESCRIPTION	BY	CHD	DATE	GLOBAL HEAT TRANSFER AUSTRALIA P/L	MATERIAL: ALUMINIUM	SCALE 1:8.75	SIZE A3	DWG No AC/41/LH621i	REV 1	
REVISIONS											